




# Pressmåttstabell

## Gates / IMM 4-lager



Slangtyp	Storlek	03	04	05	06	08	10	12	16	20	24	32	
	Tum	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	
<b>EFG3K</b> 	Hylsa 4005 Skalad									4005-20	4005-24		
											<b>50.1</b>	<b>59.0</b>	
												54	62
<b>EFG4K</b> 	Hylsa 4005 Skalad					4005-08	4005-10	4005-12	4005-16				
						<b>26.2</b>	<b>30.1</b>	<b>33.2</b>	<b>41.8</b>				
						28	27	32	47				
<b>EFG5K</b> 	Hylsa 4005 Skalad					4005-08	4005-10	4005-12	4005-16				
						<b>26.3</b>	<b>30.0</b>	<b>33.4</b>	<b>42.7</b>				
						25	29	32	48				

OBS! I applikationer med vridningsrörelser på slangenheten bör Gates Gs-kopplingar användas!

HYLSA  
ART.NR

**PRESSMÅTT**

SKALLÄNGD

Pressmåttan ovan skall ses som en vägledning som bör ge en invändig kollaps 0,3 - 3,0 mm. För att säkerställa att rätt kollaps erhållits bör kopplingarna tolkas, där möjlighet finnes.

