



Pressmåttstabell


Interlock IMM




SLANGTYP	STORLEK	03	04	05	06	08	10	12	16	20	24	32
	TUM	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"

4SP 	Hylsa 46005												
										46005-12	46005-16		
										33.0	41.2		
										15	17		
								52	64				

4SH 	Hylsa 46005													
										46005-12	46005-16	46005-20	46005-24	46005-32
										33.0	41.2	50.5	56.8	72.7
										15	17	22	22.5	30
								52	64	74	81	85		

R13 	Hylsa 46005/46006													
										46005-12	46005-16	46006-20	46006-24	46006-32
										34.1	41.5	54.2	60.5	77.9
										15	17	22	22.5	30
								52	64	74	81	85		

R15 	Hylsa 46005/46006													
										46005-12	46005-16	46006-20	46006-24	46006-32
										33.0	41.5	54.2	60.5	77.9
										15	17	22	22.5	30
								52	64	74	81	85		

Pressmåten ovan skall ses som en vägledning som bör ge en invändig kollaps 0.15 - 0.50 mm.

HYLSA ART.NR	PRESSMÅTT	SKALLÄNGD INVÄNDIGT	SKALLÄNGD UTVÄNDIGT
-----------------	------------------	------------------------	------------------------

