





Pressmåttstabell

Syrafast Gates 4-lager

SLANGTYP	STORLEK	06	08	10	12	16	20	24	32	
	TUM	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	
EFG3K 	Hylsa 4005-SY Skalad						4005-20-SY	4005-24-SY	4005-32-SY	
							51.6	59.4	72.4	
							45	49	60	
EFG4K 	Hylsa 4005-SY Skalad			4005-10-SY	4005-12-SY	4005-16-SY	4005-20-SY			
				29.9	34.3	42.2	50.8			
				27	31	38	45			
EFG5K 	Hylsa 4005-SY Skalad		4005-08-SY	4005-10-SY						
				26.8	29.6					
				23.5	27					
	Interlock 46005-SY 46006-SY Skalad						46005-16-SY	46006-20-SY	46006-24-SY	46006-32-SY
							42.6	54.6	64.0	79.0
							18	21	24	26
					57	64	77	82		
EFG6K 	Hylsa 4005-SY Skalad	4005-06-SY	4005-08-SY	4005-10-SY						
			23.3	26.8	29.8					
			23	23.5	27					
	Interlock 46005-SY 46006-SY Skalad						46005-16-SY	46006-20-SY	46006-24-SY	46006-32-SY
							42.8	54.4	64.0	79.0
							18	21	24	26
					57	64	77	82		

Pressmåten ovan skall ses som en vägledning som bör ge en invändig kollaps 0.3 - 3.0 mm.
För att säkerställa att rätt kollaps erhållits bör kopplingarna tolkas, där möjlighet finnes.

HYLSA ART.NR	PRESSMÅTT	SKALLÄNGD INVÄNDIGT	SKALLÄNGD UTVÄNDIGT
-----------------	------------------	------------------------	------------------------

