


Pressmåttstabell


Tvättslang

SLANGTYP	STORLEK	04	05	06	08
	TUM	1/4"	5/16"	3/8"	1/2"


HP250 / HPS250	Hylsa 001C Skalfri	001C-04	001C-05	001C-06	001C-08
		15.2	16.7	19.5	22.6
	Hylsa 4000 Skalad			4000-06	
				20.0	
				24	
G-koppling	G-koppl.		G-koppl.		
	17.9		21.2		
		D21		D22	



HP400 / HPS400	Hylsa 001C Skalfri	001C-04	001C-05	001C-06	001C-08
		16.1	17.7	20.4	23.2
	Hylsa 4000 Skalad			4000-06	4000-08
				21.6	24.8
				23	24
Hylsa 0021-SY Skalad			0021-06-SY	0021-08-SY	
			20.2	24.6	
G-koppling			G-koppl.	G-koppl.	
			20.9	25.4	
			D22	D33	



2PC XX B	Hylsa 0022 Skalfri			0022-06	
				20.7	
	Hylsa 4000 Skalad				4000-08
					25.4
					25
Hylsa 0021-SY Skalad			0021-06-SY		
			21.1		
G-koppling			G-koppl.		
			22.5		
			D22		



Pressmåten ovan skall ses som en vägledning som bör ge en invändig kollaps 0,15 - 0,50 mm. G-kopplingar pressas med rekommenderade Gates-pressbackar.

HYLSA ART.NR	PRESSMÅTT	SKALLÄNGD	PRESSBACK
-----------------	------------------	-----------	-----------



PRESSMÅTT KAN ÄNDRAS.
SÄKERSTÄLL UTSKRIFTENS GILTIGHET.

Denna version ersätter alla tidigare utgåvor.
Revisionsdatum 2018-04-17